



US 20240244876A1

(19) **United States**

(12) **Patent Application Publication**

KIM et al.

(10) **Pub. No.: US 2024/0244876 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)

(72) Inventors: **KwangJong KIM**, Seoul (KR); **Jisu MOON**, Seoul (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(21) Appl. No.: **18/396,447**

(22) Filed: **Dec. 26, 2023**

(30) **Foreign Application Priority Data**

Jan. 13, 2023 (KR) ..... 10-2023-0005393

**Publication Classification**

(51) **Int. Cl.**

*H10K 50/828* (2006.01)

*H10K 50/818* (2006.01)

*H10K 59/122* (2006.01)

*H10K 59/80* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H10K 50/828* (2023.02); *H10K 50/818* (2023.02); *H10K 59/122* (2023.02); *H10K 59/878* (2023.02)

(57) **ABSTRACT**

A display device includes a transistor above a substrate, a planarization layer above the transistor and having a first open area, an anode electrode in the first open area as well as a side portion and a part of a top surface of the planarization layer opposite to the first open area, a bank covering a part of the anode electrode and having a second open area corresponding to the first open area, an organic layer on the anode electrode exposed by the second open area, a cathode electrode on the organic layer, and a capping layer above the cathode electrode and including a first capping layer having a first refractive index, a second capping layer having a second refractive index, and a third capping layer having a third refractive index. The first refractive index and the third refractive index are relatively lower than the second refractive index.