



US 20240235485A1

(19) **United States**(12) **Patent Application Publication**  
**KOGURE et al.**(10) **Pub. No.: US 2024/0235485 A1**(43) **Pub. Date: Jul. 11, 2024**(54) **TRACKER MODULE AND  
COMMUNICATION DEVICE****Publication Classification**

(51) **Int. Cl.**  
*H03F 1/02* (2006.01)  
*H03F 3/24* (2006.01)  
(52) **U.S. Cl.**  
CPC ..... *H03F 1/0233* (2013.01); *H03F 3/245*  
(2013.01); *H03F 2200/105* (2013.01); *H03F*  
*2200/451* (2013.01)

(71) Applicant: **Murata Manufacturing Co., Ltd.**,  
Nagaokakyo-shi (JP)  
(72) Inventors: **Takeshi KOGURE**, Nagaokakyo-shi  
(JP); **Tomohide ARAMATA**,  
Nagaokakyo-shi (JP); **Yuuki FUKUDA**,  
Nagaokakyo-shi (JP); **Toshiki**  
**MATSUI**, Nagaokakyo-shi (JP)

(21) Appl. No.: **18/616,654**(22) Filed: **Mar. 26, 2024****Related U.S. Application Data**(63) Continuation of application No. PCT/JP2022/  
035971, filed on Sep. 27, 2022.**Foreign Application Priority Data**

Sep. 29, 2021 (JP) ..... 2021-159654

(57) **ABSTRACT**

A tracker module includes a module laminate, a first integrated circuit and a second integrated circuit on the module laminate, and a capacitor disposed on the module laminate and included in a switched-capacitor circuit. The switched-capacitor circuit is configured to generate discrete voltages based on an input voltage. The first integrated circuit includes a switch included in the switched-capacitor circuit. The second integrated circuit includes a switch included in at least one of a supply modulator and a pre-regulator circuit. The supply modulator is configured to selectively output at least one of the discrete voltages based on an envelope signal. The pre-regulator circuit is configured to convert the input voltage into a first voltage and output the first voltage to the switched-capacitor circuit. A distance between the first integrated circuit and the capacitor is shorter than a distance between the second integrated circuit and the capacitor.

