

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0235493 A1

Jul. 11, 2024 (43) **Pub. Date:**

(54) FEEDFORWARD AMPLIFIER CIRCUIT, AUDIO AMPLIFIER AND AUDIO PLAYING DEVICE

(71) Applicant: GUANGZHOU TOPPING TECHNOLOGY CO., LTD.,

Guangzhou, Guangdong (CN)

(72) Inventors: Yueqiu HE, Guangdong (CN); Hetian

YANG, Guangdong (CN)

(73) Assignee: GUANGZHOU TOPPING

ELECTRONIC AND TECHNOLOGY CO., LTD.,

Guangdong (CN)

(21) Appl. No.: 17/800,619

(22) PCT Filed: May 17, 2021

(86) PCT No.: PCT/CN2021/094208

§ 371 (c)(1),

Aug. 18, 2022 (2) Date:

Publication Classification

(51) Int. Cl.

H03F 1/34 (2006.01)H03F 1/26 (2006.01) H03F 3/187 (2006.01)H03F 3/45 (2006.01)

(52) U.S. Cl.

CPC H03F 1/34 (2013.01); H03F 1/26 (2013.01); H03F 3/187 (2013.01); H03F 3/45475 (2013.01); H03F 2200/03 (2013.01); H03F 2201/3218 (2013.01)

(57)**ABSTRACT**

Provided are feedforward amplifier circuit, audio amplifier and audio playing device, including: a main amplifier circuit, an adder circuit, a sub-amplifier circuit and a subtractor circuit, wherein the main amplifier circuit adds distortion to a first input signal to output a distorted signal, and inputs the distorted signal to the adder circuit and the subtractor circuit for performing feedforward correction; the sub-amplifier circuit amplifies a second input signal and serves as a positive input of the subtractor, so that a signal gain output by the subtractor is equal to a signal gain of the main amplifier; the subtractor circuit, with the distorted signal as a negative input, reversely amplifies the distorted signal and afterwards performs feedforward; and the adder circuit superimposes the distorted signal output by the main amplifier circuit and the reversely amplified distorted signal output by the subtractor, so as to output a distortion-free signal.

