



US 20240237405A1

(19) **United States**

(12) **Patent Application Publication**
Wang et al.

(10) **Pub. No.: US 2024/0237405 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **ARRAY SUBSTRATE AND DISPLAY APPARATUS**

Publication Classification

(71) Applicants: **Chengdu BOE Optoelectronics Technology Co., Ltd.**, Chengdu (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(51) **Int. Cl.**
H10K 59/121 (2006.01)
H10K 59/122 (2006.01)
H10K 59/131 (2006.01)
H10K 59/35 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/1213** (2023.02); **H10K 59/1216** (2023.02); **H10K 59/122** (2023.02); **H10K 59/131** (2023.02); **H10K 59/351** (2023.02); **H10K 59/353** (2023.02)

(72) Inventors: **Siyu Wang**, Beijing (CN); **Yi Zhang**, Beijing (CN); **Qian Ma**, Beijing (CN); **Junxiu Dai**, Beijing (CN)

(73) Assignees: **Chengdu BOE Optoelectronics Technology Co., Ltd.**, Chengdu (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(21) Appl. No.: **18/616,392**

(22) Filed: **Mar. 26, 2024**

Related U.S. Application Data

(63) Continuation of application No. 17/428,969, filed on Aug. 5, 2021, now Pat. No. 11,974,463, filed as application No. PCT/CN2020/121752 on Oct. 19, 2020.

(57) **ABSTRACT**

An array substrate is provided. The array substrate includes a plurality of light emitting elements respectively in a plurality of subpixels; and a plurality of pixel driving circuits respectively in the plurality of subpixels configured to respectively drive the plurality of light emitting elements. Multiple pixel driving circuits of the plurality of pixel driving circuits are arranged along a first direction. A respective one of the pixel driving circuits includes a third transistor. A width, along the first direction, of a third anode of a third light emitting element in a respective third subpixel is no less than a distance, along the first direction, between two adjacent third transistors in two adjacent pixel driving circuits of the multiple pixel driving circuits.

