



US 20240213454A1

(19) **United States**

(12) **Patent Application Publication**
LEE et al.

(10) **Pub. No.: US 2024/0213454 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ELECTRODE PLATE FOR RECHARGEABLE BATTERY, MANUFACTURING METHOD THEREOF, AND RECHARGEABLE BATTERY USING THE SAME**

(71) Applicant: **SAMSUNG SDI CO., LTD.**, Yongin-si (KR)

(72) Inventors: **Taeil LEE**, Yongin-si (KR); **Won-Gi AHN**, Yongin-si (KR); **Juhye BAE**, Yongin-si (KR); **Gwangwon PARK**, Yongin-si (KR); **Min-young JEONG**, Yongin-si (KR)

(21) Appl. No.: **18/469,416**

(22) Filed: **Sep. 18, 2023**

(30) **Foreign Application Priority Data**

Dec. 26, 2022 (KR) 10-2022-0184839

Publication Classification

(51) **Int. Cl.**

H01M 4/36 (2006.01)

H01M 4/04 (2006.01)

H01M 4/38 (2006.01)

H01M 4/587 (2006.01)

(52) **U.S. Cl.**

CPC **H01M 4/366** (2013.01); **H01M 4/0404** (2013.01); **H01M 4/0471** (2013.01); **H01M 4/386** (2013.01); **H01M 4/587** (2013.01)

(57)

ABSTRACT

An electrode plate includes an electrode current collector; a first active material layer in a pattern at the electrode current collector; and a second active material layer covering first active material layer and a portion of the electrode current collector. The electrode plate for a rechargeable battery may improve an impregnation characteristic of an electrolyte by inducing bending in a width direction of the electrode plate to improve rate capability.

