



US 20240213941A1

(19) **United States**

(12) **Patent Application Publication**
Nguyen et al.

(10) **Pub. No.: US 2024/0213941 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **VARIABLE GAIN OPTICAL MODULATOR
WITH OPEN COLLECTOR DRIVER
AMPLIFIER AND METHOD OF OPERATION**

(52) **U.S. Cl.**
CPC *H03F 3/607* (2013.01); *H03F 1/565*
(2013.01); *H03F 3/45085* (2013.01); *H03G*
1/0029 (2013.01)

(71) Applicant: **MACOM Technology Solutions
Holdings, Inc., Lowell, MA (US)**

(57) **ABSTRACT**

(72) Inventors: **Nguyen Nguyen**, Lowell, MA (US);
Duy Nguyen, Lowell, MA (US); **Trong
Phan**, Lowell, MA (US); **Thanh Pham**,
Lowell, MA (US); **Wayne Kennan**,
Lowell, MA (US); **Stefano D'Agostino**,
Los Altos, CA (US)

A distributed amplifier system comprising an impedance matching network configured to match an input impedance to an output impedance of the signal source, and a DC block configured to block DC components in the input signal. A variable gain amplifier adjusts the gain applied to the input signal based on a gain control signal to generate a gain adjusted signal. An emitter follower circuit receives and processes the gain adjusted signal to introduce gain peaking to create a modified signal. A distributed amplifier receives and amplifies the modified signal from the emitter follower circuit, to create an amplified signal. The distributed amplifier includes a termination network and one or more impedance matching elements configured for gain shaping the amplified signal. The gain peaking introduced by the emitter follower circuit is controlled by a variable current source. The distributed amplifier may be an open collector distributed amplifier.

(21) Appl. No.: **18/089,421**

(22) Filed: **Dec. 27, 2022**

Publication Classification

(51) **Int. Cl.**
H03F 3/60 (2006.01)
H03F 1/56 (2006.01)
H03F 3/45 (2006.01)
H03G 1/00 (2006.01)

