



US 20240237196A9

(19) **United States**
(12) **Patent Application Publication**
YOSHIDA et al.

(10) **Pub. No.: US 2024/0237196 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **FLEXIBLE WIRING BOARD,
MANUFACTURING METHOD, ELECTRONIC
MODULE, ELECTRONIC UNIT, AND
ELECTRONIC APPARATUS**

(71) Applicant: **CANON KABUSHIKI KAISHA,**
Tokyo (JP)

(72) Inventors: **TOSHIYUKI YOSHIDA,** Kanagawa
(JP); **YU OGAWA,** Tokyo (JP)

(21) Appl. No.: **18/490,597**

(22) Filed: **Oct. 19, 2023**

Prior Publication Data

(15) Correction of US 2024/0138057 A1 Apr. 25, 2024
See (22) Filed
See (30) Foreign Application Data

(65) US 2024/0138057 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 24, 2022 (JP) 2022-169813

Publication Classification

(51) **Int. Cl.**
H05K 1/02 (2006.01)
H04N 23/54 (2006.01)
H05K 1/14 (2006.01)
H05K 3/12 (2006.01)
(52) **U.S. Cl.**
CPC **H05K 1/028** (2013.01); **H04N 23/54**
(2023.01); **H05K 1/147** (2013.01); **H05K**
3/1216 (2013.01); **H05K 2201/10151**
(2013.01)

(57) **ABSTRACT**

A flexible wiring board includes a signal line that transmits a signal and an electroconductive layer that is disposed to face the signal line, wherein the electroconductive layer includes a first portion in which a plurality of openings are provided, and a linear second portion that is formed in at least one of the plurality of openings, that has, at one end thereof, a connection portion connected to the first portion, and whose other end is an open end, where the connection portion is disposed in the second portion on a sending side in a transmission direction of a signal through the signal line. An angle between a direction along the transmission direction of the signal and an extension direction of the second portion from the connection portion toward the open end is an acute angle or an obtuse angle.

