



US 20240179831A1

(19) **United States**

(12) **Patent Application Publication**
YAMAGUCHI et al.

(10) **Pub. No.: US 2024/0179831 A1**

(43) **Pub. Date: May 30, 2024**

(54) **ELECTRONIC MODULE AND ELECTRONIC DEVICE**

(71) Applicant: **CANON KABUSHIKI KAISHA**,
Tokyo (JP)

(72) Inventors: **HIROYUKI YAMAGUCHI**,
Kanagawa (JP); **MOMOKA UMEGAE**, Kanagawa (JP)

(21) Appl. No.: **18/515,661**

(22) Filed: **Nov. 21, 2023**

(30) **Foreign Application Priority Data**

Nov. 28, 2022 (JP) 2022-189005

Publication Classification

(51) **Int. Cl.**
H05K 1/02 (2006.01)
H05K 1/11 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 1/0262** (2013.01); **H05K 1/112**
(2013.01); **H04N 25/709** (2023.01); **H05K**
2201/0335 (2013.01); **H05K 2201/0776**
(2013.01)

(57)

ABSTRACT

An electronic module includes a plurality of loads, a first wiring portion, a second wiring portion, a power source unit, and a feedback portion. The first wiring portion includes a plurality of first portions to which the plurality of loads are respectively connected, and a plurality of second portions each closest to a corresponding one of the plurality of first portions. The second wiring portion is connected to the plurality of second portions. The power source unit includes a feedback terminal, an output terminal, and a power source circuit. In the first wiring portion, a minimum path length from each of the plurality of second portions to the corresponding one of the plurality of first portions is smaller than 1/2 of a minimum path length from a part of the first wiring portion connected to the output terminal to the corresponding one of the plurality of first portions.

