

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0237510 A1 GAO et al.

Jul. 11, 2024 (43) **Pub. Date:**

(54) ORGANIC LIGHT-EMITTING DIODE STRUCTURE AND DISPLAY DEVICE

(71) Applicant: BOE Technology Group Co., Ltd.,

Beijing (CN)

(72) Inventors: Rongrong GAO, Beijing (CN); Lei

CHEN, Beijing (CN)

17/913,791 (21) Appl. No.:

(22) PCT Filed: Nov. 9, 2021

(86) PCT No.: PCT/CN2021/129588

§ 371 (c)(1),

(2) Date: Sep. 22, 2022

(30)Foreign Application Priority Data

Apr. 6, 2021 (CN) 202110367717.X

Publication Classification

(51) Int. Cl.

H10K 85/60 (2023.01)H10K 50/11 (2023.01) H10K 50/16 (2023.01)H10K 101/40 (2023.01)H10K 101/60 (2023.01)

(52) U.S. Cl.

CPC H10K 85/615 (2023.02); H10K 85/624 (2023.02); H10K 85/626 (2023.02); H10K 85/654 (2023.02); H10K 85/6574 (2023.02); H10K 50/11 (2023.02); H10K 50/16 (2023.02); H10K 2101/40 (2023.02); H10K 2101/60 (2023.02)

(57)**ABSTRACT**

The present disclosure provides an organic light-emitting diode structure and a display device. In the organic lightemitting diode structure, the light-emitting layer, the hole blocking layer and the electron blocking layer satisfy the following conditions: T1 (HBL)>T1 (Host); T1 (EBL)>T1 (Host); T1 (Dopant)>T1 (Host); S1 (Host)>S1 (Dopant); wherein T1 (HBL) is the lowest triplet energy of the hole blocking layer material, T1 (Host) is the lowest triplet energy of the host material, T1 (EBL) is the lowest triplet energy of the electron blocking layer material, T1 (Dopant) is the lowest triplet energy of the guest material, S1 (Host) is the lowest singlet energy of the host material, and S1 (Dopant) is the lowest singlet energy of the guest material.

