



US 20240213780A1

(19) **United States**

(12) **Patent Application Publication**
NAKAMURA et al.

(10) **Pub. No.: US 2024/0213780 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **STORAGE BATTERY CONTROL DEVICE**

Publication Classification

(71) Applicant: **NTT DOCOMO, INC.**, Chiyoda-ku (JP)

(72) Inventors: **Masaki NAKAMURA**, Chiyoda-ku (JP); **Yuta TOYAMA**, Chiyoda-ku (JP); **Kazuhiko TAKENO**, Chiyoda-ku (JP)

(73) Assignee: **NTT DOCOMO, INC.**, Chiyoda-ku (JP)

(21) Appl. No.: **18/554,669**

(22) PCT Filed: **Feb. 24, 2022**

(86) PCT No.: **PCT/JP2022/007695**

§ 371 (c)(1),

(2) Date: **Oct. 10, 2023**

(30) **Foreign Application Priority Data**

May 10, 2021 (JP) 2021-079645

(51) **Int. Cl.**

H02J 3/32 (2006.01)

H02J 7/00 (2006.01)

H02J 7/04 (2006.01)

H02J 13/00 (2006.01)

(52) **U.S. Cl.**

CPC **H02J 3/32** (2013.01); **H02J 7/0013**

(2013.01); **H02J 7/0048** (2020.01); **H02J 7/04**

(2013.01); **H02J 13/00006** (2020.01)

(57)

ABSTRACT

A storage battery control device that can perform more flexible control of storage batteries is provided. The storage battery control device 1 includes a control unit 10 configured to perform at least one of first control and second control when it is detected that a charging/discharging criterion for responding to a demand response (DR) request is not satisfied after one or more storage batteries 3 have been determined as a control object of charging/discharging for responding to the DR request, wherein the first control utilizes a storage battery 3 other than the control object, and the second control utilizes a storage battery 3 with a surplus charging/discharging capacity after responding to the DR request out of the storage batteries 3 which are the control object.

