



US 20240213757A1

(19) **United States**(12) **Patent Application Publication**
Miller, III(10) **Pub. No.: US 2024/0213757 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **SYSTEM AND METHOD FOR DISCERNING
ARCING IN ELECTRICAL WIRING****Publication Classification**(51) **Int. Cl.***H02H 1/04* (2006.01)*H02H 1/00* (2006.01)*H02H 3/10* (2006.01)*H02H 3/33* (2006.01)(52) **U.S. Cl.**CPC *H02H 1/043* (2013.01); *H02H 1/0015*(2013.01); *H02H 3/10* (2013.01); *H02H 3/33*

(2013.01)

(71) Applicant: **Hubbell Incorporated**, Shelton, CT
(US)(72) Inventor: **William Vernon Miller, III**, Aldie, VA
(US)(21) Appl. No.: **18/432,999**(22) Filed: **Feb. 5, 2024****Related U.S. Application Data**(63) Continuation of application No. 17/527,789, filed on
Nov. 16, 2021, now Pat. No. 11,894,668, which is a
continuation of application No. 16/520,679, filed on
Jul. 24, 2019, now Pat. No. 11,183,831.(60) Provisional application No. 62/703,127, filed on Jul.
25, 2018.

(57)

ABSTRACT

A wiring device may include an interrupting device configured to be placed in a tripped condition. A wiring device may include a controller having an electronic processor and a memory, the controller configured to identify a presence of an in-rush condition conforming with a decay progression envelope falling between an upper limit and a lower limit specific to a cycle's position in sequence, and prevent the tripped condition upon identifying the in-rush condition.

