

(19) **United States**(12) **Patent Application Publication**
JIN et al.(10) **Pub. No.: US 2024/0251613 A1**(43) **Pub. Date: Jul. 25, 2024**(54) **DISPLAY DEVICE AND METHOD OF
FABRICATING THE SAME**(52) **U.S. Cl.**CPC *H10K 59/131* (2023.02); *H10K 59/1201*
(2023.02); *H10K 59/88* (2023.02); *H10K*
2102/3026 (2023.02)(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-Si
(KR)(72) Inventors: **Guanghai JIN**, Yongin-si (KR); **Yong**
Seog KIM, Yongin-si (KR)(21) Appl. No.: **18/383,049**(22) Filed: **Oct. 24, 2023**(30) **Foreign Application Priority Data**

Jan. 25, 2023 (KR) 10-2023-0009292

Publication Classification(51) **Int. Cl.***H10K 59/131* (2006.01)*H10K 59/12* (2006.01)*H10K 59/88* (2006.01)(57) **ABSTRACT**

The present disclosure relates to a display device and a method of fabricating the same. According to an embodiment of the disclosure, a display device comprising a plurality of sub-pixels formed in a display area of a display panel, a plurality of gate lines and a plurality of data lines electrically connected to the plurality of sub-pixels, a plurality of fan-out lines formed in a non-display area of the display panel to be electrically connected to the plurality of data lines, a plurality of gate control lines electrically connected to a gate driver formed in the non-display area, and at least one line number identification pattern formed on at least one line among the plurality of gate lines, the plurality of data lines, the plurality of fan-out lines, and the plurality of gate control lines, wherein the line number identification pattern represents a line number for the at least one line.

10