



US 20240237527A1

(19) **United States**

(12) **Patent Application Publication**
WATABE et al.

(10) **Pub. No.: US 2024/0237527 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **LIGHT-EMITTING DEVICE, DISPLAY APPARATUS, DISPLAY MODULE, AND ELECTRONIC DEVICE**

H10K 50/17 (2023.01)

H10K 59/131 (2023.01)

H10K 59/35 (2023.01)

H10K 85/30 (2023.01)

(71) Applicant: **SEMICONDUCTOR ENERGY LABORATORY CO., LTD.**, Atsugi-shi (JP)

(52) **U.S. Cl.**

CPC *H10K 85/6572* (2023.02); *H10K 50/131*

(2023.02); *H10K 50/171* (2023.02); *H10K*

59/131 (2023.02); *H10K 59/352* (2023.02);

H10K 85/342 (2023.02); *H10K 85/6576*

(2023.02)

(72) Inventors: **Takeyoshi WATABE**, Atsugi (JP);
Hideko YOSHIKUMI, Atsugi (JP);
Nobuharu OHSAWA, Zama (JP);
Hiromi SEO, Sagamihara (JP); **Toshiki SASAKI**, Kawasaki (JP)

(57)

ABSTRACT

A novel light-emitting device that is highly convenient, useful, or reliable is provided. The light-emitting device includes a first electrode, a second electrode, a first unit, and a first layer. The first unit is positioned between the first electrode and the second electrode and contains a first light-emitting material. The first layer is positioned between the second electrode and the first unit and contains a first organic compound and a second organic compound. The first organic compound has an acid dissociation constant pK_a larger than or equal to 8, and the second organic compound has no pyridine ring, no phenanthroline ring, or one phenanthroline ring.

(21) Appl. No.: **18/541,411**

(22) Filed: **Dec. 15, 2023**

(30) Foreign Application Priority Data

Dec. 23, 2022 (JP) 2022-206180

Publication Classification

(51) **Int. Cl.**

H10K 85/60 (2023.01)

H10K 50/13 (2023.01)

