



(12) **Patent Application Publication**
Son et al.

(43) **Pub. Date:** **May 30, 2024**

Publication Classification

(51) **Int. Cl.**
H10K 59/122 (2006.01)
H10K 59/12 (2006.01)
H10K 59/80 (2006.01)

(52) **U.S. Cl.**
 CPC *H10K 59/122* (2023.02); *H10K 59/1201*
 (2023.02); *H10K 59/80521* (2023.02)

(57) **ABSTRACT**

A display apparatus includes a first sub-pixel electrode, a conductive bank layer including a first opening overlapping the first sub-pixel electrode in a plan view, an insulating layer between a peripheral portion of the first sub-pixel electrode and the conductive bank layer, a first intermediate layer disposed on the first sub-pixel electrode in the first opening of the conductive bank layer, and a first counter electrode disposed on the first intermediate layer in the first opening of the conductive bank layer. The conductive bank layer comprises a first conductive layer, a second conductive layer on the first conductive layer, and a third conductive layer on the second conductive layer. The first counter electrode has a width greater than a width of the first intermediate layer. The first counter electrode is in direct contact with the conductive bank layer.

(22) Filed: **Nov. 27, 2023**

(30) **Foreign Application Priority Data**

Nov. 30, 2022 (KR) 10-2022-0165101

