US 20240244938A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0244938 A1**

LI et al. (43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **InnoLux Corporation**, Miao-Li County (TW)

(72) Inventors: **Wen-Tse LI**, Miao-Li County (TW); **Shih-Fu LIAO**, Miao-Li County (TW); **I-An YAO**, Miao-Li County (TW)

(21) Appl. No.: **18/539,817**

(22) Filed: **Dec. 14, 2023**

(30) **Foreign Application Priority Data**

Jan. 13, 2023 (CN) 202310039158.9

Publication Classification

(51) **Int. Cl.**
H10K 59/80 (2006.01)

(52) **U.S. Cl.**
CPC ***H10K 59/879*** (2023.02); ***H10K 59/8792*** (2023.02)

(57) **ABSTRACT**

A display device includes a first substrate, a light emitting unit and a first micro lens unit. The light emitting unit is arranged on the first substrate to provide a light. The first micro lens unit is arranged on the light emitting unit to adjust the traveling direction of the light, wherein there is a distance from the light emitting surface of the light emitting unit to a position of half the height of the first micro lens unit, the first micro lens unit has an arc surface, the first micro lens unit has a height, and the arc surface has a curvature radius, and the distance and the curvature radius satisfy the relationship: $0.5H \leq D \leq 3R1$, where D represents the distance, H represents the height, and R1 represents the curvature radius.