



US 20240215246A1

(19) **United States**

(12) **Patent Application Publication**
Lengade et al.

(10) **Pub. No.: US 2024/0215246 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **METHODS OF FORMING
MICROELECTRONIC DEVICES WITH
NITROGEN-RICH INSULATIVE
STRUCTURES, AND RELATED MEMORY
DEVICES AND ELECTRONIC SYSTEMS**

Publication Classification

(51) **Int. Cl.**
H10B 43/27 (2006.01)
H01L 21/02 (2006.01)
H10B 41/27 (2006.01)
(52) **U.S. Cl.**
CPC *H10B 43/27* (2023.02); *H01L 21/0217*
(2013.01); *H01L 21/02266* (2013.01); *H01L*
21/02274 (2013.01); *H10B 41/27* (2023.02)

(71) Applicant: **Micron Technology, Inc.**, Boise, ID
(US)

(72) Inventors: **Swapnil A. Lengade**, Boise, ID (US);
Jeremy Adams, Boise, ID (US);
Naiming Liu, Boise, ID (US); **Jeslin J.**
Wu, Boise, ID (US); **Kadir Abdul**,
Singapore (SG); **Carlo Mendoza**
Orofeo, Singapore (SG)

(21) Appl. No.: **18/596,580**

(22) Filed: **Mar. 5, 2024**

Related U.S. Application Data

(62) Division of application No. 17/200,169, filed on Mar.
12, 2021.

(57) **ABSTRACT**

A method of forming a microelectronic device comprises forming a stack structure comprising a vertically alternating sequence of insulative structures and additional insulative structures, at least some of the additional insulative structures comprising silicon nitride having a ratio of nitrogen atoms to silicon atoms greater than about 1.58:1.00, forming openings through the stack structure, and forming cell pillar structures within the openings, the cell pillar structures individually comprising a semiconductor channel material vertically extending through the stack structure. Related methods, microelectronic devices, memory devices, and electronic systems are also described.

