



(19) **United States**

(12) **Patent Application Publication**  
JIN et al.

(10) **Pub. No.: US 2024/0213490 A1**

(43) **Pub. Date:** Jun. 27, 2024

(54) **COPPER FOIL CAPABLE OF PREVENTING TEAR OR WRINKLE DEFECTS, ELECTRODE COMPRISING THE SAME, SECONDARY BATTERY COMPRISING THE SAME, AND METHOD FOR MANUFACTURING THE SAME**

(71) Applicant: **SK NEXILIS CO., LTD.**, Jeongeup-si Jeollabuk-do (KR)

(72) Inventors: **Shan Hua JIN**, Jeongeup-si Jeollabuk-do (KR); **Min Seok YOON**, Jeongeup-si Jeollabuk-do (KR)

(21) Appl. No.: **18/392,730**

(22) Filed: **Dec. 21, 2023**

(30) **Foreign Application Priority Data**

Dec. 27, 2022	(KR)	10-2022-0185255
Oct. 5, 2023	(KR)	10-2023-0132912

**Publication Classification**

(51) **Int. Cl.**  
*H01M 4/66* (2006.01)  
*H01M 4/134* (2006.01)  
*H01M 4/75* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *H01M 4/661* (2013.01); *H01M 4/134* (2013.01); *H01M 4/667* (2013.01); *H01M 4/75* (2013.01); *H01M 10/0525* (2013.01)

(57) **ABSTRACT**

According to one embodiment of the present disclosure, there is provided a copper foil including a copper film including 99.9 wt % or more of copper, wherein the copper foil has a first stress factor in a range of 2.8 to 3.2, a second stress factor in a range of 2.5 to 3.0, and a third stress factor in a range of 3.5 to 4.5, and a method for manufacturing the copper foil.

