



US 20240237222A1

(19) **United States**

(12) **Patent Application Publication**
KIM et al.

(10) **Pub. No.: US 2024/0237222 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DRIVING CHIP ACCOMMODATING
CIRCUIT BOARD AND DISPLAY DEVICE
HAVING THE SAME**

H05K 1/02 (2006.01)

H10K 59/90 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 1/189** (2013.01); **H01L 25/18**
(2013.01); **H05K 1/0209** (2013.01); **H05K**
1/0218 (2013.01); **H10K 59/90** (2023.02);
H05K 2201/0715 (2013.01); **H05K**
2201/09036 (2013.01); **H05K 2201/09063**
(2013.01); **H05K 2201/10128** (2013.01)

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(72) Inventors: **HYEONJI KIM**, Yongin-si (KR);
JUYEOP SEONG, Yongin-si (KR);
HEE-KWON LEE, Yongin-si (KR)

(21) Appl. No.: **18/364,578**

(22) Filed: **Aug. 3, 2023**

(57)

ABSTRACT

(30) **Foreign Application Priority Data**

Jan. 10, 2023 (KR) 10-2023-0003559

Publication Classification

(51) **Int. Cl.**

H05K 1/18 (2006.01)

H01L 25/18 (2006.01)

A display device includes a display substrate including a display area, a pixel in the display area, a pad area adjacent to the display area, and a pad in the pad area, a driving chip on the display substrate, in the pad area, and a circuit board which is on the display substrate and electrically connected to the display substrate at the pad, the circuit board defining a groove of the circuit board and covering the driving chip at the groove.

