



US 20240237432A9

(19) **United States**
(12) **Patent Application Publication**
KONG et al.

(10) **Pub. No.: US 2024/0237432 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **DISPLAY SUBSTRATE, PREPARATION METHOD THEREFOR, AND DISPLAY DEVICE**

Publication Classification

(71) Applicants: **Chengdu BOE Optoelectronics Technology Co., Ltd.**, Chengdu, Sichuan (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(51) **Int. Cl.**
H10K 59/131 (2006.01)
H10K 59/12 (2006.01)
H10K 59/122 (2006.01)
H10K 59/35 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/131** (2023.02); **H10K 59/1201** (2023.02); **H10K 59/122** (2023.02); **H10K 59/353** (2023.02)

(72) Inventors: **Chao KONG**, Beijing (CN); **Yifan YANG**, Beijing (CN); **Wei ZHANG**, Beijing (CN)

(21) Appl. No.: **17/768,841**

(57) **ABSTRACT**

(22) PCT Filed: **Jul. 5, 2021**

(86) PCT No.: **PCT/CN2021/104525**

§ 371 (c)(1),

(2) Date: **Apr. 13, 2022**

Prior Publication Data

(15) Correction of US 2024/0138210 A1 Apr. 25, 2024
See (22) PCT Filed.
See (86) PCT No.
See (30) Foreign Application Priority Data.

(65) US 2024/0138210 A1 Apr. 25, 2024

Foreign Application Priority Data

Aug. 28, 2020 (CN) 202010892357.0

A display substrate, including: a base substrate. The base substrate includes a display region, and the display region is provided with a plurality of sub-pixels and a conductive protective structure. At least one sub-pixel among the plurality of sub-pixels includes: a light-emitting element and a driving circuit that drives the light-emitting element to emit light. The light-emitting elements and the conductive protective structure are located on the side of the driving circuit away from the base substrate. The conductive protective structure includes at least one conductive part, and the at least one conductive part is located at an interval between respective light-emitting parts of light-emitting elements of at least two adjacent sub-pixels. The conductive protective structure is electrically connected to a signal terminal, and is configured to reduce carrier transmission between adjacent sub-pixels.

