

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231680 A1

Jul. 20, 2023 (43) **Pub. Date:**

(54) REFERENCE SIGNAL TRANSITION FOR RADIO LINK MONITORING AND BEAM FAILURE DETECTION

(71) Applicant: APPLE INC., CUPERTINO, CA (US)

(72) Inventors: Jie CUI, San Jose, CA (US); Dawei ZHANG, Saratoga, CA (US); Haitong SUN, Cupertino, CA (US); Hong HE, San Jose, CA (US); Huaning NIU, San Jose, CA (US); Manasa RAGHAVAN, Sunnyvale, CA (US); Qiming LI, Beijing (CN); Xiang CHEN, Campbell, CA (US); Yang TANG, San Jose, CA (US); Yushu ZHANG, Beijing (CN)

(21) Appl. No.: 17/441,856

(22) PCT Filed: May 7, 2021 (86) PCT No.: PCT/CN2021/092074

§ 371 (c)(1),

Sep. 22, 2021 (2) Date:

Publication Classification

(51) Int. Cl. H04L 5/00 (2006.01)(2006.01) H04W 24/08 H04W 76/28 (2006.01)

(52) U.S. Cl. CPC H04L 5/0051 (2013.01); H04W 24/08 (2013.01); H04W 76/28 (2018.02)

(57)ABSTRACT

The present application relates to devices and components including apparatus, systems, and methods for radio link monitoring and/or beam failure detection operations in wireless communication systems.

in a first DRX mode, using an evaluation period having a first duration for evaluating a downlink radio link quality on a BFD-RS

404

400

at a first time, transitioning from the first DRX mode to a second DRX mode that is different from the DRX mode <u>408</u>

using a mixed evaluation period for evaluating a downlink radio link quality on the BFD-RS, wherein the mixed evaluation period begins prior to the first time and ends after the first time

412