



US 20240213532A1

(19) **United States**

(12) **Patent Application Publication**
Cho

(10) **Pub. No.: US 2024/0213532 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **SEMISOLID ELECTROLYTE MEMBRANE
AND METHOD OF FABRICATION THEREOF**

(71) Applicant: **Soelect Inc.**, Greensboro, NC (US)

(72) Inventor: **Sungjin Cho**, Summerfield, NC (US)

(21) Appl. No.: **18/571,869**

(22) PCT Filed: **Mar. 17, 2022**

(86) PCT No.: **PCT/US2022/020836**

§ 371 (c)(1),

(2) Date: **Dec. 19, 2023**

Related U.S. Application Data

(60) Provisional application No. 63/163,445, filed on Mar. 19, 2021.

Publication Classification

(51) **Int. Cl.**

H01M 10/0565 (2006.01)

H01M 10/0525 (2006.01)

(52) **U.S. Cl.**

CPC ... **H01M 10/0565** (2013.01); **H01M 10/0525**
(2013.01); **H01M 2300/0082** (2013.01); **H01M**
2300/0085 (2013.01); **H01M 2300/0094**
(2013.01)

(57)

ABSTRACT

Disclosed herein is a unique semisolid electrolyte structure for utilization within energy storage devices (batteries, capacitors, and the like). Such a semisolid exhibits, simultaneously, flexibility and electrolyte transfer capabilities, thereby allowing for the potential, at least, for such a semisolid article to function as both a battery (or like device) separator and electrolyte supply. Such characteristics and capabilities are imparted through the initial provision of a base substrate that exhibits swelling upon contact with a viscous polymer electrolyte solution, thereby allowing for a first electrolyte to deposit therein opened pores within the swollen base. A second treatment with solid electrolyte may then fill any further open pores therein, allowing for a complete separator/electrolyte article that removes the requirement for liquid, flammable electrolytes, thereby providing a safer device. The manufacturing method is relatively simple and encompassed herein as well.

