



US 20240179947A1

(19) **United States**

(12) **Patent Application Publication**
Kang et al.

(10) **Pub. No.: US 2024/0179947 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME**

Publication Classification

(51) **Int. Cl.**

H10K 59/121 (2006.01)

H10K 59/12 (2006.01)

(52) **U.S. Cl.**

CPC H10K 59/1213 (2023.02); **H10K 59/1201** (2023.02)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventors: **Pilgyu Kang**, Yongin-si (KR); **Younghoon Yoo**, Yongin-si (KR); **Euna Yu**, Yongin-si (KR); **Jeonghyun Lee**, Yongin-si (KR); **Hanul Lee**, Yongin-si (KR); **Sangcheon Han**, Yongin-si (KR)

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(21) Appl. No.: **18/454,310**

(22) Filed: **Aug. 23, 2023**

(30) **Foreign Application Priority Data**

Nov. 29, 2022 (KR) 10-2022-0163247

(57)

ABSTRACT

A display apparatus includes a semiconductor layer disposed on a substrate and including a channel area, a source area and a drain area that are disposed at both sides of the channel area, and a first opening portion disposed adjacent to the source area or the drain area, and a first electrode overlapping and electrically connected to the source area or the drain area and including an edge adjacent to the first opening portion. The edge of the first electrode is concave in a direction from the first opening portion toward the source area or the drain area.

