



US 20240237493A1

(19) **United States**(12) **Patent Application Publication**
CHANG et al.(10) **Pub. No.: US 2024/0237493 A1**(43) **Pub. Date: Jul. 11, 2024**(54) **DISPLAY DEVICE AND MANUFACTURING METHOD****Publication Classification**(51) **Int. Cl.****H10K 59/80**

(2006.01)

H10K 71/20

(2006.01)

H10K 71/60

(2006.01)

(52) **U.S. Cl.**CPC **H10K 59/873** (2023.02); **H10K 71/231** (2023.02); **H10K 71/60** (2023.02)

(57)

ABSTRACT

A display device including a first lower electrode disposed on a base layer, an insulating film disposed on the base layer, a conductive barrier rib disposed on the insulating film and having a first opening defined therein and corresponding to a light-emitting region, a first light-emitting pattern disposed on the first lower electrode inside the first opening, a first upper electrode disposed on the first light-emitting pattern and contacting an inner side surface of the conductive barrier rib defining the first opening, and a first inorganic encapsulation pattern, disposed in the first opening, and contacting the inner side surface of the conductive barrier rib, wherein a central portion of an upper surface of the first inorganic encapsulation pattern and a peripheral portion surrounding the central portion of the upper surface of the first inorganic encapsulation pattern may form a step difference.

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)(72) Inventors: **CHONGSUP CHANG**, Yongin-si (KR); **YOUNGSEOK BAEK**, Yongin-si (KR); **INKYUNG YOO**, Yongin-si (KR); **YONGHAN LEE**, Yongin-si (KR)(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)(21) Appl. No.: **18/489,937**(22) Filed: **Oct. 19, 2023**(30) **Foreign Application Priority Data**

Jan. 6, 2023 (KR) 10-2023-0002032

