

## (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2024/0251542 A1

Jul. 25, 2024 (43) **Pub. Date:** 

### (54) SEMICONDUCTOR DEVICE AND METHOD OF MANUFACTURING THE SAME

(71) Applicant: NANYA TECHNOLOGY **CORPORATION**, New Taipei City (TW)

Wen-Chieh WANG, Taoyuan City (72) Inventor: (TW)

(21) Appl. No.: 18/156,417

(22) Filed: Jan. 19, 2023

#### **Publication Classification**

(51) **Int. Cl.** H10B 12/00 (2006.01)

#### (52) U.S. Cl. CPC ...... H10B 12/03 (2023.02)

#### ABSTRACT (57)

The present disclosure provides a method of manufacturing a semiconductor device. The method includes: sequentially forming a first supporting layer, a first mold layer, and a second supporting layer on a surface of a substrate; forming a plurality of first openings on the second supporting layer to expose the first mold layer; sequentially forming a second mold layer and a third supporting layer on the second supporting layer including the first openings; forming a plurality of second openings on the third supporting layer to expose the second mold layer; filling a mold material in the second openings; forming a plurality of trenches to expose the substrate, and the trenches are separated from the second openings; conformally forming a conductive layer on inner sidewalls of the trenches; and removing the mold material, the second mold layer, and the first mold layer.

M

sequentially forming a first supporting layer, a first mold layer, and a second supporting layer on a surface of a substrate, in which the first mold layer is formed sandwiched between the first supporting layer and the second supporting layer

~ S101

forming a plurality of first openings on the second supporting layer to expose the first mold layer

-S102

sequentially forming a second mold layer and a third supporting layer on the second supporting layer including the first openings, so that the second mold layer contacts the first mold layer

- S103

