



US 20240179952A1

(19) **United States**

(12) **Patent Application Publication**  
**Zhang et al.**

(10) **Pub. No.: US 2024/0179952 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAYING BASE PLATE AND  
MANUFACTURING METHOD THEREOF,  
AND DISPLAYING DEVICE**

**H10K 59/80** (2006.01)

**H10K 102/00** (2006.01)

(52) **U.S. Cl.**

**CPC** ..... **H10K 59/122** (2023.02); **H10K 59/1201**  
(2023.02); **H10K 59/873** (2023.02); **H10K**  
**2102/311** (2023.02)

(71) Applicant: **BOE Technology Group Co., Ltd.**,  
Beijing (CN)

(72) Inventors: **Ziyu Zhang**, Beijing (CN); **Tao Sun**,  
Beijing (CN); **Chengjie Qin**, Beijing  
(CN); **Pinfan Wang**, Beijing (CN)

(73) Assignee: **BOE Technology Group Co., Ltd.**,  
Beijing (CN)

(21) Appl. No.: **17/793,980**

(22) PCT Filed: **Sep. 28, 2021**

(86) PCT No.: **PCT/CN2021/121357**

§ 371 (c)(1),

(2) Date: **Jul. 20, 2022**

**Publication Classification**

(51) **Int. Cl.**

**H10K 59/122** (2006.01)

**H10K 59/12** (2006.01)

(57) **ABSTRACT**

A displaying base plate and a manufacturing method thereof, and a displaying device. The displaying base plate includes an opening area and an isolation area surrounding the opening area, the isolation area includes: a first flexible substrate and at least one isolation slot provided on one side of the first flexible substrate, and the isolation slot is formed by a first inorganic film layer, an organic film layer and a second inorganic film layer that are disposed in stack; the first inorganic film layer is disposed close to the first flexible substrate, and the first inorganic film layer has a first surface facing the opening area; the organic film layer is provided on one side of the first inorganic film layer that is away from the first flexible substrate, and the organic film layer has a second surface facing the opening area.

