



US 20230232157A1

(19) **United States**(12) **Patent Application Publication**
LIU et al.(10) **Pub. No.: US 2023/0232157 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **APPLICATION DEVICE****Publication Classification**(71) Applicant: **GOERTEK INC.**, Weifang, Shandong (CN)(72) Inventors: **Chunfa LIU**, Weifang, Shandong (CN);
Jianbin YANG, Weifang, Shandong (CN); **Jianxin WANG**, Weifang, Shandong (CN); **Shousong QIANG**, Weifang, Shandong (CN)(51) **Int. Cl.****H04R 9/04** (2006.01)**H04R 9/06** (2006.01)**H04R 7/04** (2006.01)(52) **U.S. Cl.**CPC **H04R 9/043** (2013.01); **H04R 9/06** (2013.01); **H04R 7/04** (2013.01); **H04R 9/025** (2013.01)(21) Appl. No.: **17/999,883**(22) PCT Filed: **Nov. 7, 2020**(86) PCT No.: **PCT/CN2020/127326**

§ 371 (c)(1),

(2) Date: **Nov. 25, 2022**(30) **Foreign Application Priority Data**

May 25, 2020 (CN) 202010458487.3

ABSTRACT

Disclosed is an application device comprising a plurality of elastic members, the elastic member comprises a first connecting portion, a second connecting portion and a deformation portion located between the first connecting portion and the second connecting portion; the first connecting portion and the second connecting portion are connected to different components in the application device respectively, and the different components are movable relative to each other, or the different components may be unmovable relative to each other; the deformation portion is formed by extending from the first end to the second end along the same direction or different directions in a straight line and/or a curved line; and each of the elastic members is integrally formed by punching a sheet-shaped structure.

