US 20220385289A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0385289 A1

WATANABE et al. (43) Pub. Date: Dec. 1, 2022

(54) **INTEGRATED CIRCUIT, CIRCUIT BOARD, AND ELECTRONIC APPARATUS**

(71) Applicant: **Oki Electric Industry Co., Ltd.**, Tokyo (JP)

(72) Inventors: **Keisuke WATANABE**, Tokyo (JP); **Yohei OGAWA**, Tokyo (JP); **Yukio ITO**, Tokyo (JP)

(73) Assignee: **Oki Electric Industry Co., Ltd.**, Tokyo (JP)

(21) Appl. No.: **17/748,798**

(22) Filed: **May 19, 2022**

(30) **Foreign Application Priority Data**

May 24, 2021 (JP) 2021-087037
Oct. 26, 2021 (JP) 2021-174914

Publication Classification

(51) **Int. Cl.**
H03K 19/00 (2006.01)
H03K 19/003 (2006.01)
H05K 1/02 (2006.01)

(52) **U.S. Cl.**
CPC ... ***H03K 19/0005*** (2013.01); ***H03K 19/00369*** (2013.01); ***H05K 1/0246*** (2013.01); *H01L 23/64* (2013.01)

(57) **ABSTRACT**

An integrated circuit according to one or more embodiments may include a terminal to which an impedance element and a power supply having a predetermined potential can be connected. The integrated circuit may be configured to change a potential of one of electrodes of the impedance element connected to the terminal, detect a change in electrical characteristics of the terminal based on characteristics of the impedance element when the potential of the one electrode of the impedance element is changed, to determine a setting condition among a plurality of setting conditions that are used for an operation of the integrated circuit, store the setting condition in a storage, and use the setting condition stored in the storage for the operation of the integrated circuit.