



US 20230230752A1

(19) **United States**(12) **Patent Application Publication****Kim et al.**(10) **Pub. No.: US 2023/0230752 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **COIL COMPONENT****H01F 41/10** (2006.01)**H01F 41/12** (2006.01)(71) Applicant: **SAMSUNG**
ELECTRO-MECHANICS CO., LTD.,
Suwon-si (KR)(52) **U.S. Cl.**
CPC **H01F 27/292** (2013.01); **H01F 27/323**
(2013.01); **H01F 41/10** (2013.01); **H01F**
41/122 (2013.01)(72) Inventors: **Young Ji Kim**, Suwon-si (KR); **Kwang**
Sun Choi, Suwon-si (KR); **Jin Ho Ku**,
Suwon-si (KR)(57) **ABSTRACT**(73) Assignee: **SAMSUNG**
ELECTRO-MECHANICS CO., LTD.,
Suwon-si (KR)(21) Appl. No.: **17/824,560**(22) Filed: **May 25, 2022**(30) **Foreign Application Priority Data**

Jan. 14, 2022 (KR) 10-2022-0005827

Publication Classification(51) **Int. Cl.**
H01F 27/29 (2006.01)
H01F 27/32 (2006.01)

According to an aspect of the present disclosure, a coil component includes: a body having a first surface and a second surface opposing each other in a first direction, and a plurality of side surfaces connecting the first surface and the second surface to each other; a substrate disposed in the body; at least one insulating pattern disposed on at least one corner where two of the plurality of side surfaces of the body are in contact with each other and exposed to the two side surfaces of the body; a coil unit including a coil pattern disposed on at least one surface of the substrate with a plurality of turns, and lead-out portions respectively exposed to opposing ones of the plurality of side surfaces of the body; and external electrodes disposed on the body and connected to the lead-out portions, respectively.

