US 20220360152A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0360152 A1

Watanabe et al. (43) Pub. Date: Nov. 10, 2022

(54) MOTOR AND METHOD OF MANUFACTURING STATOR

(71) Applicant: **SINFONIA TECHNOLOGY CO., LTD.**, Tokyo (JP)

(72) Inventors: **Shunya Watanabe**, Tokyo (JP); **Nobuo Aruga**, Tokyo (JP); **Mamoru Kosaki**, Tokyo (JP); **Masayasu Kayukawa**, Tokyo (JP)

(73) Assignee: **SINFONIA TECHNOLOGY CO., LTD.**, Tokyo (JP)

(21) Appl. No.: **17/623,514**

(22) PCT Filed: **Jun. 26, 2020**

(86) PCT No.: **PCT/JP2020/025194**

§ 371 (c)(1),
(2) Date: **Dec. 28, 2021**

(30) **Foreign Application Priority Data**

Jul. 4, 2019 (JP) 2019-125091

Publication Classification

(51) **Int. Cl.**

H02K 15/12	(2006.01)
H02K 9/19	(2006.01)
H02K 3/28	(2006.01)
H02K 3/12	(2006.01)
H02K 3/24	(2006.01)

(52) **U.S. Cl.**

CPC ***H02K 15/12*** (2013.01); ***H02K 9/19*** (2013.01); ***H02K 3/28*** (2013.01); ***H02K 3/12*** (2013.01); ***H02K 3/24*** (2013.01)

(57) **ABSTRACT**

It is possible to reduce a rise in temperature of a rotor by reducing the temperature of a stator. The motor **1** includes a stator **5**, and a rotor **4**, which is disposed with a gap from the stator **5**, being arranged in a housing **2**, in which the stator **5** is provided with an annular yoke and a plurality of teeth protruding from an inner peripheral portion of the yoke toward the rotor **4**; slots in which coils **6** wound around the teeth are arranged are respectively formed between the teeth that are adjacent to each other; a mold resin portion **30** in which the stator **5** and the coils **6** are molded is provided; the mold resin portion **30** includes a flow path **32** formed within at least one slot among a plurality of slots; and the flow path **32** is supplied with a cooling medium.