

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213279 A1

TOMEKAWA et al. (43) **Pub. Date:**

Jun. 27, 2024

(54) IMAGE SENSOR INCLUDING CONTROL ELECTRODE, TRANSPARENT ELECTRODE, AND CONNECTION LAYER ELECTRICALLY CONNECTING CONTROL ELECTRODE TO SIDE SURFACE OF TRANSPARENT ELECTRODE

(71) Applicant: Panasonic Intellectual Property Management Co., Ltd., Osaka (JP)

Inventors: Yuuko TOMEKAWA, Osaka (JP); Katsuya NOZAWA, Kyoto (JP)

(21) Appl. No.: 18/598,856

(22) Filed: Mar. 7, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/095,691, filed on Nov. 11, 2020, now Pat. No. 11,955,493, which is a continuation of application No. PCT/JP2019/020662, filed on May 24, 2019.

(30)Foreign Application Priority Data

Jun. 14, 2018 (JP) 2018-113447

Publication Classification

(51) Int. Cl. H01L 27/146 (2006.01)H10K 39/32 (2006.01)

(52)U.S. Cl. CPC .. H01L 27/14605 (2013.01); H01L 27/14636 (2013.01); H10K 39/32 (2023.02)

ABSTRACT (57)

An image sensor includes pixel electrodes, a control electrode, a photoelectric conversion film arranged on the pixel electrodes, a transparent electrode arranged on the photoelectric conversion film, an insulating layer arranged on at least a portion of a top surface of the transparent electrode, and a connection layer that electrically connects the control electrode to the transparent electrode. The connection layer is in contact with at least one side surface of the transparent electrode. A side surface of the insulating layer, the at least one side surface of the transparent electrode, and a side surface of the photoelectric conversion film are aligned with each other.

