

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0214109 A1

Zhang et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) SYSTEM AND METHOD FOR PHASE TRACKING REFERENCE SIGNAL DYNAMIC PRESENCE IN ULTRA-RELIABLE AND LOW-LATENCY AND PORT INDICATION

(71) Applicant: Apple Inc., Cupertino, CA (US)

(72) Inventors: Yushu Zhang, Beijing (CN); Gang

Xiong, Portland, OR (US); Yujian Zhang, Beijing (CN); Guotong Wang,

Beijing (CN)

(21) Appl. No.: 17/420,407

PCT Filed: Jan. 8, 2020

(86) PCT No.: PCT/US2020/012800

§ 371 (c)(1),

Jul. 2, 2021 (2) Date:

(30)Foreign Application Priority Data

Jan. 10, 2019 (WO) PCT/CN2019/071188

Publication Classification

(51) Int. Cl. H04L 1/00

(2006.01)

U.S. Cl. (52)

CPC H04L 1/0025 (2013.01); H04L 1/0004

(57)ABSTRACT

A user equipment wireless communication device in a wireless communication environment receives a signal from the network that includes a radio network temporary ID. From the radio network temporary ID, the user equipment is capable of determining whether a phase tracking reference signal is present based on the radio network temporary ID. If any of these are identified by the radio network temporary ID, then the user equipment determines that a phase tracking reference signal is present. After the user equipment has determined that the phase tracking reference signal is present, the user equipment can then determine which phase tracking reference signal antenna ports are to be used based on the values of the transmitted precoding matrix indicator value and the transmit rank indicator.

200

