



US 20230231159A1

(19) **United States**(12) **Patent Application Publication**  
**Kemmer et al.**(10) **Pub. No.: US 2023/0231159 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **HEAT EXCHANGER SYSTEM FOR  
OPERATING A FUEL CELL STACK**(52) **U.S. Cl.**CPC .... *H01M 8/04014* (2013.01); *H01M 8/04111*  
(2013.01); *H01M 8/04335* (2013.01); *H01M*  
*8/04753* (2013.01)(71) Applicant: **Robert Bosch GmbH**, Stuttgart (DE)(72) Inventors: **Helerson Kemmer**, Vaihingen (DE);  
**Jochen Braun**, Heimsheim (DE)

(57)

**ABSTRACT**(21) Appl. No.: **18/007,793**(22) PCT Filed: **May 21, 2021**(86) PCT No.: **PCT/EP2021/063675**

§ 371 (c)(1),

(2) Date: **Dec. 2, 2022**(30) **Foreign Application Priority Data**

Jun. 3, 2020 (DE) ..... 10 2020 206 918.2

**Publication Classification**(51) **Int. Cl.***H01M 8/04014* (2006.01)*H01M 8/04111* (2006.01)*H01M 8/0432* (2006.01)*H01M 8/04746* (2006.01)

The invention relates to a heat exchanger system for operating a fuel cell stack, comprising: a first compressor and a second compressor for the cathode gas fed to the fuel cell stack, the second compressor being fluidically downstream of the first compressor; a turbine, which is mechanically coupled to the second compressor and against which the cathode gas discharged from the fuel cell stack flows; a first heat exchanger, which is thermally coupled to the fed cathode gas between the first compressor and the second compressor; a second heat exchanger, which is thermally coupled to the fed cathode gas downstream of the second compressor; a fourth heat exchanger, which is thermally coupled to the discharged cathode gas downstream of the turbine; wherein the fourth heat exchanger is thermally variably coupled to the first heat exchanger and to the second heat exchanger in order to control a heat exchange for cooling the first heat exchanger and the second heat exchanger.

