US 20240237458A9

(19) **United States**

(12) **Patent Application Publication**

LIU et al.

(10) **Pub. No.: US 2024/0237458 A9**

(48) **Pub. Date: Jul. 11, 2024**

CORRECTED PUBLICATION

(54) **DISPLAY SUBSTRATE AND DISPLAY APPARATUS**

(71) Applicants: **Chengdu BOE Optoelectronics Technology Co., Ltd.**, Chengdu, Sichuan (CN); **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(72) Inventors: **Xiaonan LIU**, Beijing (CN); **Jun LI**, Beijing (CN); **Changsoon JI**, Beijing (CN); **Tinghua SHANG**, Beijing (CN); **Qian XU**, Beijing (CN)

(21) Appl. No.: **18/279,048**

(22) PCT Filed: **Aug. 24, 2022**

(86) PCT No.: **PCT/CN2022/114390**

§ 371 (c)(1),
(2) Date: **Aug. 25, 2023**

Prior Publication Data

(15) Correction of US 2024/0138222 A1 Apr. 25, 2024
See (86) PCT No.

(65) US 2024/0138222 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Aug. 31, 2021 (CN) 202111014705.5

Publication Classification

(51) **Int. Cl.**
H10K 59/35 (2006.01)
H10K 59/122 (2006.01)
H10K 59/80 (2006.01)

(52) **U.S. Cl.**
CPC ***H10K 59/353*** (2023.02); ***H10K 59/122*** (2023.02); ***H10K 59/8723*** (2023.02)

(57) **ABSTRACT**

The present disclosure provides a display substrate and a display apparatus, belongs to the field of display technology, and at least partially solves one existing technical problem. The display substrate includes a base substrate, and sub-pixels in an array at intervals on the base substrate; wherein the adjacent sub-pixels are provided with a spacer region therebetween; the spacer region includes a first spacer region having a functional position, and a second spacer region having no functional position; at least some functional positions are provided with functional parts; and a width of the first spacer region between two adjacent sub-pixels arranged along the first direction or the second direction is greater than that of the second spacer region between two adjacent sub-pixels arranged along the same direction; wherein a width of the spacer region is equal to a shortest distance between boundaries of the two sub-pixels corresponding to the spacer region.