

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231108 A1 HONG et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) POSITIVE ELECTRODE FOR LITHIUM-SULFUR SECONDARY BATTERY, AND LITHIUM-SULFUR SECONDARY **BATTERY COMPRISING SAME**

(71) Applicants: LG ENERGY SOLUTION, LTD., Seoul (KR); GWANGJU INSTITUTE

OF SCIENCE AND TECHNOLOGY,

Gwangju (KR)

(72) Inventors: **Kyungsik HONG**, Daejeon (KR);

Kwangsup EOM, Gwangju (KR); Hayong SONG, Gwangju (KR); Dongseok SHIN, Daejeon (KR); Kwonnam SOHN, Daejeon (KR); Yun

Kyoung KIM, Daejeon (KR); Seungmin LEE, Gwangju (KR)

18/010,767 (21) Appl. No.:

PCT Filed: (22)Oct. 18, 2021

(86) PCT No.: PCT/KR2021/014506

§ 371 (c)(1),

(2) Date: Dec. 15, 2022

(30)Foreign Application Priority Data

(KR) 10-2020-0137322 Oct. 22, 2020

Publication Classification


(51) Int. Cl. H01M 4/36 (2006.01)H01M 10/052 (2006.01)H01M 4/62 (2006.01)H01M 4/583 (2006.01)

U.S. Cl. (52)

> H01M 4/364 (2013.01); H01M 10/052 CPC (2013.01); H01M 4/622 (2013.01); H01M 4/583 (2013.01); H01M 4/624 (2013.01); H01M 2004/028 (2013.01)

(57)ABSTRACT

Provided is a positive electrode for a lithium-sulfur secondary battery comprising a positive electrode active material, an electrically conductive material, a binder, and a multivalent metal salt. The multivalent metal salt comprises a cation of a metal selected from a group consisting of metals having 3 to 6 of an effective nuclear charge of outermost electrons in the 3rd and 4th periods. The positive electrode for the lithium-sulfur secondary battery can improve the performance of the lithium-sulfur secondary battery by introducing a multivalent metal salt and thus effectively inhibiting the leaching of lithium polysulfide when applied to the battery while not significantly increasing the weight of the electrode and not significantly lowering the conductivity of the electrode.



Temperature (°C)