



US 20240237472A1

(19) **United States**

(12) **Patent Application Publication**
PARK et al.

(10) **Pub. No.: US 2024/0237472 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY DEVICE INCLUDING CAPPING
PATTERN AND METHOD OF
MANUFACTURING THE SAME**

(71) Applicant: **Samsung Display Co. Ltd.**, Yongin-si
(KR)

(72) Inventors: **Yong-hwan PARK**, Cheonan-si (KR);
Miyoung Kim, Daegu (KR); **Jongseok
Kim**, Yongin-si (KR)

(21) Appl. No.: **18/421,958**

(22) Filed: **Jan. 24, 2024**

Related U.S. Application Data

(63) Continuation of application No. 18/071,457, filed on
Nov. 29, 2022, now Pat. No. 11,910,689, which is a
continuation of application No. 17/066,766, filed on
Oct. 9, 2020, now Pat. No. 11,527,583, which is a
continuation of application No. 16/516,772, filed on
Jul. 19, 2019, now Pat. No. 10,804,338, which is a
continuation of application No. 15/659,561, filed on
Jul. 25, 2017, now Pat. No. 10,361,254.

Foreign Application Priority Data

Jul. 29, 2016 (KR) 10-2016-0097477

Publication Classification

(51) **Int. Cl.**
H10K 59/40 (2006.01)
G06F 1/16 (2006.01)
G06F 3/041 (2006.01)
G06F 3/044 (2006.01)

H01L 27/12 (2006.01)
H10K 10/88 (2006.01)
H10K 50/844 (2006.01)
H10K 59/122 (2006.01)
H10K 59/124 (2006.01)
H10K 59/13 (2006.01)
H10K 71/00 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/40** (2023.02); **G06F 1/1652**
(2013.01); **G06F 3/0412** (2013.01); **G06F**
3/04164 (2019.05); **G06F 3/0443** (2019.05);
G06F 3/0446 (2019.05); **H10K 10/88**
(2023.02); **H10K 71/621** (2023.02); **G06F**
2203/04103 (2013.01); **G06F 2203/04112**
(2013.01); **H01L 27/12** (2013.01); **H10K**
50/8445 (2023.02); **H10K 59/122** (2023.02);
H10K 59/124 (2023.02); **H10K 59/13**
(2023.02)

(57)

ABSTRACT

A display device including a substrate having a display area
and a peripheral area defined outside the display area, a
circuit layer disposed on the substrate, a device layer dis-
posed on the display area, an encapsulation layer covering
the device layer, a touch sensing unit including at least one
touch insulating layer disposed on the encapsulation layer,
touch electrodes disposed on the encapsulation layer, and
touch signal lines connected to the touch electrodes, a first
section disposed in the peripheral area and including a first
part having a first thickness, a second part having a second
thickness less than the first thickness and overlapping the
touch signal lines, and an intermediate part connecting the
first part and the second part and being inclined, and a first
thickening pattern overlapping at least the intermediate part.

