US 20220369499A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0369499 A1**

GOTO et al. (43) **Pub. Date: Nov. 17, 2022**

(54) **HEAT DISSIPATION MEMBER AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **DENKA COMPANY LIMITED**, Tokyo (JP)

(72) Inventors: **Daisuke GOTO**, Omuta-shi (JP); **Hiroaki OTA**, Omuta-shi (JP)

(73) Assignee: **DENKA COMPANY LIMITED**, Tokyo (JP)

(21) Appl. No.: **17/425,541**

(22) PCT Filed: **Jan. 29, 2020**

(86) PCT No.: **PCT/JP2020/003090**

§ 371 (c)(1),
(2) Date: **Jul. 23, 2021**

(30) **Foreign Application Priority Data**

Jan. 30, 2019 (JP) 2019-013765

Publication Classification

(51) **Int. Cl.**

H05K 7/20	(2006.01)
F28F 21/08	(2006.01)
F28F 21/04	(2006.01)
C04B 35/575	(2006.01)
C04B 41/51	(2006.01)
C04B 41/45	(2006.01)
C04B 41/88	(2006.01)
C09K 5/14	(2006.01)
B28B 3/02	(2006.01)

(52) **U.S. Cl.**

CPC ***H05K 7/2039*** (2013.01); ***F28F 21/089*** (2013.01); ***F28F 21/04*** (2013.01); ***C04B 35/575*** (2013.01); ***C04B 41/5155*** (2013.01); ***C04B 41/4523*** (2013.01); ***C04B 41/88*** (2013.01); ***C09K 5/14*** (2013.01); ***B28B 3/025*** (2013.01); *C04B 2235/3826* (2013.01); *C04B 2235/3418* (2013.01)

(57) **ABSTRACT**

Among two main surfaces of a heat dissipation member, one main surface is curved to be convex in an outward direction and the other convex in an inward direction. When a straight line passing through both endpoints P_1 and P_2 of the curve is l_1, a point at which a distance to l_1 on the curve is maximum is P_{max}, an intersection point between l_1 and a perpendicular drawn from P_{max} to l_1 is P_3, a middle point of a line segment P_1P_3 is P_4, an intersection point between the curve and a straight line that passes through P_4 and is perpendicular to l_1 is P_{mid}, a length of the line segment P_1P_3 is L, a length of a line segment P_3P_{max} is H, and a length of a line segment P_4P_{max} is h, (2 h/L)/(H/L) is 1.1 or more.

(b)