



US 20240178692A1

(19) **United States**

(12) **Patent Application Publication**  
**WANG et al.**

(10) **Pub. No.: US 2024/0178692 A1**

(43) **Pub. Date: May 30, 2024**

(54) **CHARGE/DISCHARGE CONTROL METHOD,  
CHARGING DEVICE, AND STORAGE  
MEDIUM**

**Publication Classification**

(51) **Int. Cl.**  
*H02J 7/00* (2006.01)  
*B60L 53/62* (2019.01)  
*H02J 7/34* (2006.01)  
(52) **U.S. Cl.**  
CPC ..... *H02J 7/00711* (2020.01); *B60L 53/62*  
(2019.02); *H02J 7/0047* (2013.01); *H02J*  
*7/0063* (2013.01); *H02J 7/00712* (2020.01);  
*H02J 7/345* (2013.01)

(71) Applicant: **Changchun Jetty Automotive  
Technology Co., Ltd., Changchun (CN)**

(72) Inventors: **Chao WANG, Changchun (CN); Jimin  
WANG, Changchun (CN)**

(21) Appl. No.: **18/577,741**

(22) PCT Filed: **Jul. 11, 2022**

(86) PCT No.: **PCT/CN2022/104904**

§ 371 (c)(1),

(2) Date: **Jan. 9, 2024**

(30) **Foreign Application Priority Data**

Jul. 23, 2021 (CN) ..... 202110839708.6

(57)

**ABSTRACT**

The present disclosure relates to the technical field of charging devices of electric vehicles, provides a charge and discharge control method, a charging device and a storage medium, the method including: obtaining a residual voltage of an output terminal after a charging circuit is disconnected; controlling a discharge load connected in parallel with the output terminal to form a discharge circuit; performing frequency adjustment and/or width adjustment and/or dead zone adjustment on the residual voltage, so as to accelerate a discharge speed of the discharge circuit. Through the present disclosure, a residual voltage on a charging device side can be released quickly and safely after a charging circuit is disconnected.

