



US 20240215290A1

(19) **United States**

(12) **Patent Application Publication**  
**NOWATARI et al.**

(10) **Pub. No.: US 2024/0215290 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **LIGHT-EMITTING ELEMENT,  
LIGHT-EMITTING DEVICE, ELECTRONIC  
DEVICE, AND LIGHTING DEVICE**

**Publication Classification**

(51) **Int. Cl.**

*H10K 50/13* (2006.01)

*B82Y 10/00* (2006.01)

*H10K 50/11* (2006.01)

*H10K 50/19* (2006.01)

*H10K 85/20* (2006.01)

*H10K 85/30* (2006.01)

*H10K 85/60* (2006.01)

*H10K 101/40* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H10K 50/13* (2023.02); *B82Y 10/00*  
(2013.01); *H10K 50/11* (2023.02); *H10K*  
*50/131* (2023.02); *H10K 50/19* (2023.02);  
*H10K 85/221* (2023.02); *H10K 85/324*  
(2023.02); *H10K 85/615* (2023.02); *H10K*  
*85/621* (2023.02); *H10K 85/626* (2023.02);  
*H10K 85/633* (2023.02); *H10K 85/636*  
(2023.02); *H10K 85/6572* (2023.02); *H10K*  
*2101/40* (2023.02)

(71) Applicant: **Semiconductor Energy Laboratory  
Co., Ltd.**, Atsugi-shi (JP)

(72) Inventors: **Hiromi NOWATARI**, Atsugi (JP);  
**Satoshi SEO**, Kawasaki (JP);  
**Nobuharu OHSAWA**, Zama (JP);  
**Takahiro USHIKUBO**, Atsugi (JP);  
**Tetsuo TSUTSUI**, Kasuga (JP)

(21) Appl. No.: **18/396,801**

(22) Filed: **Dec. 27, 2023**

**Related U.S. Application Data**

(60) Continuation of application No. 17/153,985, filed on Jan. 21, 2021, now Pat. No. 11,889,711, which is a division of application No. 16/006,024, filed on Jun. 12, 2018, now Pat. No. 10,910,579, which is a continuation of application No. 15/138,565, filed on Apr. 26, 2016, now Pat. No. 10,050,221, which is a continuation of application No. 13/951,028, filed on Jul. 25, 2013, now Pat. No. 9,343,689, which is a continuation of application No. 12/785,648, filed on May 24, 2010, now Pat. No. 8,502,202.

**Foreign Application Priority Data**

May 29, 2009 (JP) ..... 2009-131096

(57)

**ABSTRACT**

An object is to provide a light-emitting element capable of emitting light with a high luminance even at a low voltage, and having a long lifetime. The light-emitting element includes n EL layers between an anode and a cathode (n is a natural number of two or more), and also includes, between m-th EL layer from the anode and (m+1)-th EL layer (m is a natural number,  $1 \leq m \leq n-1$ ), a first layer including a first donor material in contact with the m-th EL layer, a second layer including an electron-transport material and a second donor material in contact with the first layer, and a third layer including a hole-transport material and an acceptor material in contact with the second layer and the (m+1)-th EL layer.

