

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0179977 A1 **CHOI**

May 30, 2024 (43) **Pub. Date:**

(54) DISPLAY DEVICE AND METHOD OF PROVIDING THE SAME

(71) Applicant: Samsung Display Co., LTD., Yongin-si

(72) Inventor: HAYOUNG CHOI, Hwaseong-si (KR)

(21) Appl. No.: 18/436,325

(22) Filed: Feb. 8, 2024

Related U.S. Application Data

(62) Division of application No. 17/716,277, filed on Apr. 8, 2022, now Pat. No. 11,943,980.

(30)Foreign Application Priority Data

(KR) 10-2021-0087977

Publication Classification

(51) Int. Cl.

H10K 59/131 (2006.01)H10K 59/12 (2006.01)H10K 59/80 (2006.01)

H10K 71/00 (2006.01)H10K 77/10 (2006.01)(2006.01)H10K 102/00

(52) U.S. Cl.

CPC H10K 59/131 (2023.02); H10K 59/873 (2023.02); H10K 71/00 (2023.02); H10K *59/1201* (2023.02); *H10K* 77/111 (2023.02); H10K 2102/311 (2023.02)

(57)ABSTRACT

A display device includes a display panel, a circuit board, a first conductive film, first and second lower films, and first and second adhesive layers. The display panel includes a display area and a pad area which includes a first pad part. The circuit board is attached on the display panel and includes a lead part overlapping the first pad part. The first conductive film is between the display panel and the circuit board and electrically connects the first pad part and the lead part to each other. The first and second lower films are attached to the display panel to respectively correspond to the display area and the pad area. A thickness of the second adhesive layer between the display panel and the second lower film is less than a thickness of the first adhesive layer between the display panel and the first lower film.

