



US 20240214140A1

(19) **United States**

(12) **Patent Application Publication**
LIM et al.

(10) **Pub. No.: US 2024/0214140 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **CONFIGURATION OF DATA UNIT FOR
DUPLICATE TRANSMISSION**

Publication Classification

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)

(51) **Int. Cl.**

H04L 5/00 (2006.01)

H04L 1/08 (2006.01)

H04W 84/12 (2006.01)

(72) Inventors: **Dongguk LIM**, Seoul (KR); **Jinyoung CHUN**, Seoul (KR); **Jinsoo CHOI**, Seoul (KR); **Eunsung PARK**, Seoul (KR)

(52) **U.S. Cl.**

CPC **H04L 5/0044** (2013.01); **H04L 1/08** (2013.01); **H04W 84/12** (2013.01)

(21) Appl. No.: **18/599,072**

(22) Filed: **Mar. 7, 2024**

(57)

ABSTRACT

Related U.S. Application Data

(63) Continuation of application No. 18/013,433, filed on Jan. 25, 2023, filed as application No. PCT/KR2021/008180 on Jun. 29, 2021.

The present specification proposes a technical feature for increasing a transmission range of a wireless LAN signal. The wireless LAN signal of the present specification, e.g. a transmission physical protocol data unit (PPDU), may be configured on the basis of a duplicate transmission mode. The transmission PPDU of the present specification may comprise a data unit duplicated in frequency. The data unit duplicated in frequency may be configured on the basis of a total bandwidth of the transmission PPDU. The transmission PPDU of the present specification proposes various training fields for the duplicated data unit.

(30) **Foreign Application Priority Data**

Jun. 30, 2020 (KR) 10-2020-0080521
Jul. 1, 2020 (KR) 10-2020-0081053
Jul. 2, 2020 (KR) 10-2020-0081634
Sep. 7, 2020 (KR) 10-2020-0114046

8 μ s	8 μ s	4 μ s	4 μ s						
L-LTF	L-STF	L-SIG	RL-SIG	SIG A	SIG B	STF	LTF	Data	PE