



US 20240244877A1

(19) **United States**

(12) **Patent Application Publication**
DU et al.

(10) **Pub. No.: US 2024/0244877 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY SUBSTRATE, METHOD FOR
MANUFACTURING THE SAME AND
DISPLAY DEVICE**

Publication Classification

(51) **Int. Cl.**

H10K 50/842 (2023.01)

H10K 59/131 (2023.01)

H10K 71/00 (2023.01)

H01L 25/18 (2006.01)

H10K 59/12 (2023.01)

(52) **U.S. Cl.**

CPC **H10K 50/8426** (2023.02); **H10K 59/131**

(2023.02); **H10K 71/00** (2023.02); **H01L 25/18**

(2013.01); **H10K 59/1201** (2023.02)

(71) Applicants: **CHENGDU BOE
OPTOELECTRONICS
TECHNOLOGY CO., LTD.**, Chengdu
(CN); **BOE TECHNOLOGY GROUP
CO., LTD.**, Beijing (CN)

(72) Inventors: **Lili DU**, Beijing (CN); **Hongjun
ZHOU**, Beijing (CN)

(73) Assignees: **CHENGDU BOE
OPTOELECTRONICS
TECHNOLOGY CO., LTD.**, Chengdu
(CN); **BOE TECHNOLOGY GROUP
CO., LTD.**, Beijing (CN)

(21) Appl. No.: **18/619,338**

(22) Filed: **Mar. 28, 2024**

Related U.S. Application Data

(63) Continuation of application No. 17/432,371, filed on
Aug. 19, 2021, now Pat. No. 11,974,451, filed as
application No. PCT/CN2020/118883 on Sep. 29,
2020.

(57)

ABSTRACT

A display substrate, a method for manufacturing the same and a display device. In the display substrate, a sealant region includes: a corner sealant region, a lead-in sealant region, and a first sealant region on a first side of a display area. The corner sealant region is provided with an encapsulation base layer. A non-display area is provided with a second power line, a gate drive circuit and multiple first signal lines configured to provide signals to the gate drive circuit. The second power line includes a power line corner portion and a first power line portion, the first power line portion overlaps the first sealant region, and the first power line portion extends in a first direction. A target portion of each first signal line is at least located in the corner sealant region.

