



US 20240179842A1

(19) **United States**

(12) **Patent Application Publication**  
**LUO et al.**

(10) **Pub. No.: US 2024/0179842 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAY SCREEN AND MANUFACTURING METHOD THEREOF**

**Publication Classification**

(71) Applicant: **WUHAN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD.**, Wuhan (CN)

(51) **Int. Cl.**  
**H05K 1/14** (2006.01)  
**C09J 5/00** (2006.01)  
**C09J 9/02** (2006.01)  
**G09F 9/302** (2006.01)  
**H05K 3/36** (2006.01)

(72) Inventors: **Chengsheng LUO**, Wuhan (CN); **Tiyao MA**, Wuhan (CN); **Yingchuan JIANG**, Wuhan (CN); **Wenxu XIANYU**, Wuhan (CN)

(52) **U.S. Cl.**  
CPC ..... **H05K 1/144** (2013.01); **C09J 5/00** (2013.01); **C09J 9/02** (2013.01); **H05K 3/368** (2013.01); **G09F 9/3026** (2013.01); **H05K 2201/041** (2013.01); **H05K 2201/10128** (2013.01)

(21) Appl. No.: **17/779,836**

(22) PCT Filed: **Apr. 24, 2022**

(86) PCT No.: **PCT/CN2022/088654**

§ 371 (c)(1),

(2) Date: **May 25, 2022**

(30) **Foreign Application Priority Data**

Apr. 12, 2022 (CN) ..... 202210378523.4

**ABSTRACT**

(57) A display screen and a manufacturing method thereof are disclosed. A first conductive adhesive and a second conductive adhesive are disposed between a daughter board and a mother board. A first adhesive force is formed between the first conductive adhesive and the daughter board, a second adhesive force is formed between the first conductive adhesive and the second conductive adhesive, and a third adhesive force is formed between the second conductive adhesive and the mother board. A technical problem of the daughter board and the mother board being difficult to separate for rework after assembly can be solved by allowing both the first adhesive force and the second adhesive force to be greater than the third adhesive force.

