

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0232244 A1 Dzierwa et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) SYSTEMS, METHODS, AND DEVICES FOR ELECTRONIC SPECTRUM MANAGEMENT

(71) Applicant: Digital Global Systems, Inc., Tysons Corner, VA (US)

Inventors: Ronald C. Dzierwa, Baltimore, MD

(US); Gabriel R. Garcia, Severna Park, MD (US); Daniel Carbajal, Severna

Park, MD (US)

Assignee: Digital Global Systems, Inc., Tysons (73)

Corner, VA (US)

Appl. No.: 18/124,820

(22) Filed: Mar. 22, 2023

Related U.S. Application Data

Continuation of application No. 17/388,882, filed on Jul. 29, 2021, now Pat. No. 11,617,089, which is a continuation of application No. 16/751,741, filed on Jan. 24, 2020, now Pat. No. 11,082,859, which is a continuation of application No. 16/283,211, filed on Feb. 22, 2019, now Pat. No. 10,555,180, which is a continuation of application No. 15/589,646, filed on May 8, 2017, now Pat. No. 10,219,163, which is a continuation-in-part of application No. 15/412,982, filed on Jan. 23, 2017, now Pat. No. 10,122,479, which is a continuation-in-part of application No. 14/983,690, filed on Dec. 30, 2015, now abandoned,

which is a continuation of application No. 14/788, 838, filed on Jul. 1, 2015, now Pat. No. 9,253,648, which is a continuation of application No. 14/504, 743, filed on Oct. 2, 2014, now Pat. No. 9,094,974, which is a continuation of application No. 14/273, 193, filed on May 8, 2014, now Pat. No. 8,868,004, which is a continuation of application No. 14/082, 873, filed on Nov. 18, 2013, now Pat. No. 8,805,291, which is a continuation of application No. 13/912, 683, filed on Jun. 7, 2013, now Pat. No. 9,288,683.

Provisional application No. 61/789,758, filed on Mar. (60)15, 2013.

Publication Classification

(51) Int. Cl. H04W 28/02 (2006.01)H04B 17/318 (2006.01)

(52) U.S. Cl. CPC H04W 28/0236 (2013.01); H04B 17/318 (2015.01)

ABSTRACT

Devices and methods enable optimizing a signal of interest based on identifying and analyzing the signal of interest based on radio frequency energy measurements. Signal data is compared with stored data to identify the signal of interest. Signal degradation data is calculated based on noise figure parameters, hardware parameters and environment parameters. The signal of interest is optimized based on the signal degradation data. Terrain data is also operable to be used for optimizing the signal of interest.

