



US 20220360145A1

(19) **United States**(12) **Patent Application Publication**  
**HIGASHINO et al.**(10) **Pub. No.: US 2022/0360145 A1**(43) **Pub. Date: Nov. 10, 2022**(54) **ROTATING ELECTRIC MACHINE****Publication Classification**(71) Applicant: **Mitsubishi Electric Corporation,**  
Tokyo (JP)(51) **Int. Cl.****H02K 9/22** (2006.01)**H02K 9/06** (2006.01)**H02K 11/33** (2006.01)(52) **U.S. Cl.**CPC ..... **H02K 9/227** (2021.01); **H02K 9/06**  
(2013.01); **H02K 11/33** (2016.01)(72) Inventors: **Hiroyuki HIGASHINO**, Tokyo (JP);  
**Yosuke UNO**, Tokyo (JP); **Saburo**  
**TANAKA**, Tokyo (JP); **Toshiaki**  
**KASHIHARA**, Tokyo (JP); **Yoshinobu**  
**UTSUMI**, Tokyo (JP); **Jun TAHARA**,  
Tokyo (JP); **Hiroyuki YAHARA**, Tokyo  
(JP); **Takaya MUTO**, Tokyo (JP);  
**Shota MORIKAWA**, Tokyo (JP);  
**Naohide MAEDA**, Tokyo (JP)(73) Assignee: **Mitsubishi Electric Corporation,**  
Tokyo (JP)(21) Appl. No.: **17/645,205**(22) Filed: **Dec. 20, 2021**(30) **Foreign Application Priority Data**

May 7, 2021 (JP) ..... 2021-078948

(57)

**ABSTRACT**

With an object, of providing a rotating electric machine such that a reduction in size can be achieved, and a balance between a cooling performance and vibration resistance can be achieved, a multiple of connection portions formed of a first connection portion and a second connection portion that mechanically connect a rotating electric machine main body and a power converter are provided on a non-external device connection portion side bracket in the rotating electric machine main body and a heat dissipating member in the power converter, cross-sectional centers of the first connection portion and the second connection portion are caused to be positioned farther to an inner diameter side than an outer diameter of a stator, and a power module is disposed between two connection portions neighboring in a circumferential direction.

