US 20230230967A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0230967 A1**

**KIM et al.** (43) **Pub. Date: Jul. 20, 2023**

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si (KR)

(72) Inventors: **In Woo KIM**, Asan-si (KR); **Chang Woo KWON**, Seoul (KR); **Dae Cheol KIM**, Hwaseong-si (KR); **Jong Hwan PARK**, Hwaseong-si (KR); **Yong Tae CHO**, Yongin-si (KR); **Kook Hyun CHOI**, Asan-si (KR)

(73) Assignee: **Samsung Display Co., LTD.**, Yongin-si (KR)

(21) Appl. No.: **17/889,916**

(22) Filed: **Aug. 17, 2022**

(30) **Foreign Application Priority Data**

Jan. 20, 2022 (KR) ..... 10-2022-0008380

**Publication Classification**

(51) **Int. Cl.**

| | |
|---|---|
| ***H01L 25/16*** | (2006.01) |
| ***H01L 27/12*** | (2006.01) |
| ***H01L 23/00*** | (2006.01) |

(52) **U.S. Cl.**

CPC ..... ***H01L 25/167*** (2013.01); ***H01L 27/124*** (2013.01); ***H01L 27/1288*** (2013.01); ***H01L 24/24*** (2013.01); ***H01L 24/25*** (2013.01); ***H01L 24/82*** (2013.01); *H01L 24/95* (2013.01); *H01L 2224/24051* (2013.01); *H01L 2224/24145* (2013.01); *H01L 2224/25175* (2013.01); *H01L 2224/24991* (2013.01); *H01L 2224/95133* (2013.01); *H01L 2224/82106* (2013.01); *H01L 2224/82007* (2013.01)

(57) **ABSTRACT**

A display device includes a conductive pattern on a substrate, a via layer on the conductive pattern with a via hole exposing the conductive pattern, a first electrode and a second electrode on the via layer and spaced apart from each other, a first insulating layer on the first electrode and the second electrode, a bank layer on the first insulating layer defining an emission area and a subarea, a light-emitting element on the first insulating layer, and a first connection electrode and a second connection electrode on the first insulating layer and the light-emitting element. The first connection electrode electrically contacts an end of the light-emitting element, and the second connection electrode electrically contacts another end of the light-emitting element. The bank layer includes a bank extension portion extended to the subarea and the bank extension portion overlaps at least a portion of the via hole.