US 20240213254A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0213254 A1**

JAI et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **AU Optronics (Kunshan) Co., Ltd.**, Kunshan (CN)

(72) Inventors: **PANG-HO JAI**, Suzhou City (CN); **HUNG-CHE CHENG**, Suzhou City (CN); **WEN-CHIEH CHOU**, Suzhou City (CN)

(21) Appl. No.: **17/433,708**

(22) PCT Filed: **May 25, 2020**

(86) PCT No.: **PCT/CN2020/092070**

§ 371 (c)(1),
(2) Date: **Aug. 25, 2021**

(30) **Foreign Application Priority Data**

Mar. 19, 2020 (CN) 202010179319.0

Publication Classification

(51) **Int. Cl.**
H01L 27/12 (2006.01)
H01L 27/15 (2006.01)

(52) **U.S. Cl.**
CPC ***H01L 27/1218*** (2013.01); ***H01L 27/124*** (2013.01); ***H01L 27/156*** (2013.01)

(57) **ABSTRACT**

The invention provides a display device, comprising: a first substrate having a peripheral region and a display region, a plurality of pixel units disposed in the display region; a second metal layer electrically connected to the plurality of pixel units; a first planarization layer including a plurality of bump pad groups and a plurality of opening regions; a third metal layer having a position corresponding to the plurality of opening regions; a second substrate; a light shielding layer, a first color resist layer and a second planarization layer disposed on the second substrate; a second color resist layer; wherein in the display region, the second color resist layer is adjacent to the first color resist layer, and in the peripheral region, the second color resist layer and the first color resist layer are stacked, and a position of the second color resist layer corresponds to the plurality of opening regions.