



US 20240251616A1

(19) **United States**

(12) **Patent Application Publication**
KIM et al.

(10) **Pub. No.: US 2024/0251616 A1**

(43) **Pub. Date: Jul. 25, 2024**

(54) **DISPLAY DEVICE, METHOD OF
MANUFACTURING THE SAME, AND TILED
DISPLAY DEVICE HAVING THE SAME**

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.,**
Yongin-si (KR)

(72) Inventors: **Duk Sung KIM**, Yongin-si (KR); **Jung
Hyun KWON**, Yongin-si (KR)

(21) Appl. No.: **18/439,685**

(22) Filed: **Feb. 12, 2024**

Related U.S. Application Data

(62) Division of application No. 17/119,457, filed on Dec.
11, 2020, now Pat. No. 11,903,270.

(30) **Foreign Application Priority Data**

Mar. 5, 2020 (KR) 10-2020-0027841

Publication Classification

(51) **Int. Cl.**
H10K 59/131 (2006.01)
H10K 50/813 (2006.01)

H10K 50/822 (2006.01)

H10K 59/124 (2006.01)

H10K 59/18 (2006.01)

H10K 59/38 (2006.01)

H10K 71/00 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/131** (2023.02); **H10K 50/813**

(2023.02); **H10K 50/822** (2023.02); **H10K**

59/124 (2023.02); **H10K 59/18** (2023.02);

H10K 59/38 (2023.02); **H10K 71/00** (2023.02)

(57)

ABSTRACT

A display device includes: a substrate having a display area configured to display an image; a pixel on a first surface of the substrate in the display area and including a display element layer and a pixel circuit layer; a first driver on a second surface of the substrate facing the first surface of the substrate in the display area; and a first connection portion passing through the substrate between the first surface and the second surface of the substrate in the display area to electrically connect a first signal line of the pixel circuit layer and the first driver to each other. The display element layer includes: a first electrode and a second electrode on the same layer and spaced from each other; and a light emitting element between the first electrode and the second electrode.

