



US 20240237466A9

(19) **United States**
(12) **Patent Application Publication**
KIM et al.

(10) **Pub. No.: US 2024/0237466 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **DISPLAY PANEL AND ELECTRONIC APPARATUS INCLUDING THE SAME**

Publication Classification

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(51) **Int. Cl.**
H10K 59/38 (2023.01)
G02B 27/01 (2006.01)
H10K 59/122 (2023.01)
H10K 102/00 (2023.01)
(52) **U.S. Cl.**
CPC **H10K 59/38** (2023.02); **G02B 27/0172** (2013.01); **H10K 59/122** (2023.02); **H10K 2102/351** (2023.02)

(72) Inventors: **SANG GYUN KIM**, Yongin-si (KR); **HYOMIN KO**, Yongin-si (KR); **ILHA SONG**, Yongin-si (KR); **ILSOO OH**, Yongin-si (KR)

(21) Appl. No.: **18/365,663**

(22) Filed: **Aug. 4, 2023**

Prior Publication Data

(15) Correction of US 2024/0138225 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(65) US 2024/0138225 A1 Apr. 25, 2024

Foreign Application Priority Data

Oct. 21, 2022 (KR) 10-2022-0136231
Feb. 17, 2023 (KR) 10-2023-0021235

(57) **ABSTRACT**

Provided is a display panel including a circuit layer and a display element layer above the circuit layer. The display element layer may include a first light-emitting element, a second light-emitting element, and a pixel-defining film that are spaced apart in a direction perpendicular to the thickness direction. The first light-emitting element may include an optical auxiliary layer and a conductive layer sequentially stacked between the first electrode and the hole transport region, and the second light-emitting element may omit the optical auxiliary layer and the conductive layer. The optical auxiliary layer may be spaced apart from the hole transport region with the conductive layer interposed therebetween.

