



US 20240213525A1

(19) **United States**

(12) **Patent Application Publication**  
**TANIUCHI et al.**

(10) **Pub. No.: US 2024/0213525 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **SOLID-STATE BATTERY**

(71) Applicant: **HONDA MOTOR CO., LTD.**, Tokyo  
(JP)

(72) Inventors: **Takuya TANIUCHI**, Saitama (JP);  
**Toshimitsu TANAKA**, Saitama (JP);  
**Kizashi IWAKIRI**, Saitama (JP)

(21) Appl. No.: **18/492,798**

(22) Filed: **Oct. 24, 2023**

(30) **Foreign Application Priority Data**

Dec. 26, 2022 (JP) ..... 2022-208442

**Publication Classification**

(51) **Int. Cl.**

**H01M 10/0562** (2006.01)  
**H01M 4/36** (2006.01)  
**H01M 10/052** (2006.01)  
**H01M 50/593** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H01M 10/0562** (2013.01); **H01M 4/364**  
(2013.01); **H01M 10/052** (2013.01); **H01M**  
**50/593** (2021.01)

(57)

**ABSTRACT**

Provided is a solid-state battery including: an electrode laminate in which a negative electrode mixture layer, a solid electrolyte layer, and a positive electrode mixture layer are sequentially laminated over a negative electrode current collector; a positive electrode current collector; an insulating frame provided along an outer periphery of the positive electrode mixture layer and an outer periphery of the positive electrode current collector; and a positive electrode tab. In a cross section parallel to a laminating direction of the electrode laminate and perpendicular to a direction in which the positive electrode tab extends, the solid electrolyte layer has a first region disposed inside the insulating frame and a second region disposed outside the insulating frame, and when the solid-state battery is viewed from above, an outer peripheral edge of the second region is located outside an outer peripheral edge of the first region.

