US 20230230792A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0230792 A1**

Osada et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **FUSE AND METHOD FOR MANUFACTURING FUSE**

(71) Applicant: **Pacific Engineering Corporation**, Gifu (JP)

(72) Inventors: **Kenji Osada**, Gifu (JP); **Shuya Kataoka**, Gifu (JP)

(21) Appl. No.: **18/009,982**

(22) PCT Filed: **Jun. 10, 2021**

(86) PCT No.: **PCT/JP2021/022037**

§ 371 (c)(1),
(2) Date: **Dec. 12, 2022**

(30) **Foreign Application Priority Data**

Jul. 17, 2020 (JP) 2020-122710

Publication Classification

(51) **Int. Cl.**
H01H 85/48 (2006.01)
H01H 85/175 (2006.01)
H01H 85/12 (2006.01)
H01H 69/02 (2006.01)

(52) **U.S. Cl.**
CPC ***H01H 85/48*** (2013.01); ***H01H 85/175*** (2013.01); ***H01H 85/12*** (2013.01); ***H01H 69/02*** (2013.01)

(57) **ABSTRACT**

Therefore, the invention of the present application provides a fuse in which a position and a posture of a fuse element are easily stabilized and which is easily assembled, and a method for manufacturing the fuse. A fuse including a fuse element having a fusing portion; and a casing accommodating the fusing portion; where the fuse element has a long shape extending in a longitudinal direction of the casing and at least two or more fuse elements are provided; the fuse element has one end portion side coupled to each other by a coupling portion; a first holding portion that holds the fuse element is provided in one opening of the casing; and a locking portion that locks the coupling portion of the fuse element is provided in the first holding portion.